

WILLINK



WILLINK



FINISH OPTIONS

The Willink table is available in our complete range of laminate, veneer and sustainable surfaces, standard edgebands, standard and sustainable cores and metal base options.

See finish card.

For more detail, please refer to the following reference sheets:

- Tops
- Table Bases
- Power and Accessories

DIMENSIONS

Width: 48", 60", 72"
Depth: 18", 24", 30"
Height: 29.5"

Available in custom sizes.

WORKSURFACE SPECIFICATIONS

- 1.125" table top thickness
- Standard core construction is 44lb. density particle board
- 2" radius corners standard, square edges available upon request
- 2mm vinyl edgeband applied with medium-viscosity, high-melt adhesive
- Greenguard certified High Pressure Laminate comes standard with our full range of laminate options
- Custom shapes and sizes available

BASE SPECIFICATIONS


- 1.5" outer dimension tubing
- 13 gauge thickness
- Epoxy/polyester powder-coat finish
- Available with J-trough beam constructed of Diecast aluminum

BASE SPECIFICATIONS

- 3" diameter, nylon construction
- Locking twin wheel caster with welded insert

4-TRAC POWER SPECIFICATIONS (OPTIONAL)

- 4-Wires, 2 circuits, 20 Amps each (circuit 1 and 2 only)
- Up to 13 – Duplex receptacles per circuit, 26-15 Amp duplex receptacles per power in-feed maximum
- UL/CUL listed as a manufactured wiring system.
- Miniport: 2 Simplexes, 15 Amp cord, 2 voice/data ports, UL/CUL listed



Ask about our highly sustainable options!